

# INVISILED E OUTDOOR- MODEL: AFLSE

Linear Luminaires

WAC ARCHITECTURAL

PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The InvisiLED E series IP65 outdoor light strip adopts a new dual color extrusion process, which maximizes the intensity of the strip while ensuring no color temperature drift during light output. Specially designed for small concealed grooves, edge decorations, and other places, suitable for installation and use in semi outdoor and outdoor non water environments.

## Product Features

- Body Material: Flexible copper FPCB board, high-quality extruded sleeve
- IP Rating: IP65
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: SMD
- Light power: 6W 10W 13W
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K, Ra90
- System lighting effect : 80lm/W
- SDCM: ANSI 3 Step
- Input: 24V DC
- Dimming: Supports dimming control modules such as 0-10V, DMX512, DALI, etc
- Net Weight: About 0.16Kg/M, without packaging

## Order Model

Model	LED	Length	CRI	CCT	Series
AFLSE InvisiLED E series IP65	06 6W/M	10 1M 50 5M	9 Ra90	27 2700K	G2WT
	10 10W/M			30 3000K	
	13 13W/M			35 3500K	
		40 4000K			

Example : AFLSE-0610927G2WT

\*For other color temperature and length requirements, please consult WAC

# INVISIBLE E OUTDOOR- MODEL: AFLSE




## Linear Luminaires

WAC ARCHITECTURAL

PROJECT :

TYPE :

### Accessories

Model	Describe	Picture
AFLSE-015-M	Power connection cable, male, 15cm	
AFLSE-015-F	Power connection cable, female, 15cm	
ALED-TO24-CH3-C	Installation of cable tray, PC, length 948mm	
ALED-TO24-CH5-C	Installation of cable tray, PC, length 1494mm	

### Dimensional details

